

TCH Titanium Carbon Hybrid Series

# TC-IM, TC-IM-H



## TC-IMガイド

チタンフレームとカーボン強化樹脂のハイブリッドガイド。  
磯上物竿用





### リングサイズ：

NEW 4.25

NEW 4.5-3.6~  
4.5-5.5

4.5-5.7~  
7-14.0

7H~9H



TC-IMSG					
リング素材		SiC			
リングタイプ		D	H mm	O/D mm	W mm
リング・パイプサイズ		希望小売価格(円)			
NEW	4.25 - 1.0	750	9.1	3.5	4.0
NEW	1.1	◇	◇	◇	◇
NEW	1.2	◇	◇	◇	◇
NEW	1.3	◇	◇	◇	◇
NEW	1.4	◇	◇	◇	◇
NEW	1.5	◇	◇	◇	◇
NEW	1.6	◇	9.6	4.0	◇
NEW	1.7	◇	◇	◇	◇
NEW	1.8	◇	◇	◇	◇
NEW	1.9	◇	◇	◇	◇
NEW	2.0	◇	◇	◇	◇
NEW	2.1	◇	10.1	4.5	◇
NEW	2.2	◇	◇	◇	◇
NEW	2.3	◇	◇	◇	◇
NEW	2.4	◇	◇	◇	◇
NEW	2.5	◇	◇	◇	◇
NEW	2.6	◇	10.6	5.0	◇
NEW	2.7	◇	◇	◇	◇
NEW	2.8	◇	◇	◇	◇
NEW	2.9	◇	◇	◇	◇
NEW	3.0	◇	◇	◇	◇
NEW	3.1	◇	11.1	5.5	◇
NEW	3.2	◇	◇	◇	◇
NEW	3.3	◇	◇	◇	◇
NEW	3.4	◇	◇	◇	◇
NEW	3.5	◇	◇	◇	◇
NEW	4.5 - 3.6	800	12.3	6.0	4.1
NEW	3.7	◇	◇	◇	◇
NEW	3.8	◇	◇	◇	◇
NEW	3.9	◇	◇	◇	◇
NEW	4.0	◇	◇	◇	◇
NEW	4.1	◇	12.8	6.5	◇
NEW	4.2	◇	◇	◇	◇
NEW	4.3	◇	◇	◇	◇
NEW	4.4	◇	◇	◇	◇
NEW	4.5	◇	◇	◇	◇
NEW	4.6	◇	13.3	7.0	◇
NEW	4.7	◇	◇	◇	◇
NEW	4.8	◇	◇	◇	◇
NEW	4.9	◇	◇	◇	◇
NEW	5.0	◇	◇	◇	◇
NEW	5.2	◇	13.8	7.5	◇
NEW	5.5	◇	◇	◇	◇
NEW	5.7	850	15.1	8.4	◇
NEW	6.0	◇	◇	◇	◇
NEW	6.2	◇	15.6	8.9	◇
NEW	6.5	◇	◇	◇	◇
NEW	6.7	◇	16.1	9.4	◇
NEW	7.0	◇	◇	◇	◇
NEW	7.2	◇	16.6	9.9	◇
NEW	7.5	◇	◇	◇	◇

希望小売価格(円)		H mm	O/D mm	W mm
5 - 7.7	950	18.4	10.4	4.5
8.0	◇	◇	◇	◇
8.2	◇	18.9	10.9	◇
8.5	◇	◇	◇	◇
8.7	◇	19.4	11.4	◇
9.0	◇	◇	◇	◇
9.2	◇	19.9	11.9	◇
9.5	◇	◇	◇	◇
5.5 - 9.7	1,050	21.7	12.4	4.9
10.0	◇	◇	◇	◇
10.2	◇	22.2	12.9	◇
10.5	◇	◇	◇	◇
10.7	◇	22.7	13.4	◇
11.0	◇	◇	◇	◇
11.2	◇	23.2	13.9	◇
11.5	◇	◇	◇	◇
7 - 11.7	1,250	25.8	14.6	5.5
12.0	◇	◇	◇	◇
12.2	◇	26.3	15.1	◇
12.5	◇	◇	◇	◇
12.7	◇	26.8	15.6	◇
13.0	◇	◇	◇	◇
13.2	◇	27.5	16.5	◇
13.5	◇	◇	◇	◇
13.7	◇	28.0	17.0	◇
14.0	◇	◇	◇	◇

TC-IMSG-H					
リング素材		SiC			
リングタイプ		D	H mm	O/D mm	W mm
リング・パイプサイズ		希望小売価格(円)			
7 H - 11.2	1,350	27.9	14.1	5.5	
11.5	◇	◇	◇	◇	
11.7	◇	28.4	14.6	◇	
12.0	◇	◇	◇	◇	
12.2	◇	28.9	15.1	◇	
12.5	◇	◇	◇	◇	
12.7	◇	29.3	15.6	◇	
13.0	◇	◇	◇	◇	
9 H - 13.2	1,550	32.2	16.5	6.0	
13.5	◇	◇	◇	◇	
13.7	◇	32.7	17.0	◇	
14.0	◇	◇	◇	◇	
14.2	◇	33.1	17.5	◇	
14.5	◇	◇	◇	◇	
14.7	◇	33.6	18.0	◇	
15.0	◇	◇	◇	◇	
15.2	◇	34.1	18.5	◇	
15.5	◇	◇	◇	◇	
15.7	◇	34.6	19.0	◇	
16.0	◇	◇	◇	◇	

### 素材

リング外周支脚部	パイプ
純チタン	カーボン強化樹脂

### 表記例

- ・ TC-IMSG 4.5-5.7
- ・ TC-IMSG 7H-11.2